



INK COMPATIBILITY



3529 SyntiSOL™ PSA is a tear resistant, smooth, polypropylene display film with a "low glare," satin finish, water and scratch resistant coating and a proprietary, low tack self-adhesive. The special, low tack glue allows for easy, 100% bubble free application and residue free removal on glass and other smooth, flat surfaces. For surfaces including walls and boards with raised structure, we recommend testing prior to final application.

The SyntiSOL™ family of products lay extremely flat, both on the printer and in final application. 3529 is compatible with solvent and UVC printers.

STANDARD SIZES

- Item # 3529000024J9 - 36"x100' - 3"core
- Item # 3529000029J9 - 42"x100' - 3"core
- Item # 3529000037J9 - 50"x100' - 3"core

**Custom sizing available upon request.*

3529 SyntiSOL™ PSA

8 mil Satin Self Adhesives

PHYSICAL PROPERTIES

Caliper Thickness	8 mil polypro/5 mil liner
Basis Weight	220 gsm
Finish	Satin
Whiteness	101
Opacity	96%
Gloss (60°)	15

ADVANTAGES

- EasyTack™ Proprietary Removable Adhesive
- Tear Resistant Polypropylene Base
- Kiss-Cut Liner
- Water & Scratch Resistant
- Fast Drytime

APPLICATIONS

- Wall Posters
- General Signage
- Retail Advertising
- Trade Show Graphics