

Product Specification Sheet

Jutu JFC1010-510 Front-Lit PVC Banner

Product Code	JFC1010-510
Material Type	Front-Lit PVC Flex Banner
Weight	510 g/m ² +- 5%
Base Fabric	500 x 500D, 18 x 12
Surface Finish	Glossy or Matte
Color	White (printable side), gray back
Printable Technologies	Solvent, Eco-Solvent, UV, Screen Printing
Tensile Strength	>= 2200 N/5cm (Warp), >= 2000 N/5cm (Weft)
Tear Strength	>= 250 N (Warp), >= 230 N (Weft)
Peel Strength	>= 50 N/5cm
Weather Resistance	Good UV, water, and cold resistance
Flame Retardant	Optional (B1/M1 available upon request)
Temperature Range	-20 degC to +70 degC
Ink Absorption	High ink holdout, vivid color performance
Width Availability	1.02m to 5.00m (40" to 197")
Standard Roll Length	50 meters (164 feet)
Storage Conditions	15-30 degC, 40-60% RH, avoid direct sunlight or moisture
Applications	Billboards, banners, lightboxes, tradeshow graphics, construction signs

Advantages

- Smooth surface for excellent image clarity
- Compatible with wide-format printers
- Anti-fungal, water-resistant, and UV-stable
- Suitable for indoor & outdoor use