



PT. MARGACIPTA WIRASENTOSA

Cast Acrylic Sheet & PVC Hose Manufacturer

Jl. Raya Serang Km. 16.8 Desa Telaga, Kec. Cikupa, Tangerang - Indonesia
 Tel : 62-21 59401380, 59404545, 5960647, Fax : 62-21 59405842
 Email : info@margacipta.com, Website : www.margacipta.com



Product Overview

Cast Acrylic Sheet Dimension	Foot	Inch	Mm	
	3 X 6	36.2X 72	920 X 1830	
	4 X 6	48 X 72	1220 X 1830	
	4 X 8	48 X 96	1220 X 2440	
	4.5 X 6	54.3 X 72	1380 X 1830	
	3.3 X 6.5	39.4 X 78.8	1000 X 2000	
	3.6 X 7.2	42.9 X 86.2	1090 x 2190	
	4.2 X 8.2	50 X 98	1290 X 2510	
	6.2 X 8.2	62 X 98	1880 X 2490	
	6.65 X 10	80 X 120	2030 X 3050	
Thickness	4 x 10	48 X 120	1220 X 3050	
	4.3 X 8.3	51.18 X 100	1300 X 2540	
	5 X 10	60 X 120	1525 X 3050	
	6 X 10	72 X 120	1830 X 3050	
	4.4 x 6.5	53.15 x 78.8	1350 X 2000	
		0.06 – 2	1.5 – 50	
	Finish	Clear, Opal, Transparent (tint), Intransparent (opaque/ matted), Fluorescent (Spotlight), Satin		
	Acrylic Rod/ Square	Inch	Mm	
	Length	47.25 – 78.74	1200 - 2000	
Thickness	0.2 – 1.5	5 – 38		
Acrylic Hinge	Length			
	0.79, 1.18, 1.77		20, 30, 45	
Acrylic Round Tube	Length		2000	
In-Out Diameter	78.74		6x8; 8x10; 8x12; 16x20; 21x25; 26x30; 31x35; 36x40; 41x45; 46x50; 56x60	
Acrylic Triangle/Corner	Length		1200 - 2000	
Thickness	47.25 – 78.74 0.12 – 0.31		3 - 8	
OTHER PRODUCT				
-PVC Garden Hose		-MC Bond Aluminum Composite Panel		
-PVC Corrugated Roof		-PP Twinwall Sheet		
-PVC Door		-PE Rope		

Cast Acrylic Sheet Thickness Tolerance

Thickness Inch	% Tolerance		
	standard size	large size	Extra large size
0.08	12%		
0.98	10%		
0.118	10%	14%	17%
0.177	8%	12%	14%
0.220	6%	10%	12%
0.236	6%	10%	12%
5/16	5%	8%	10%
3/8	4%	6%	8%
1/2	4%	6%	8%
5/8	4%	6%	8%
3/4	4%		
1	4%		
above	4%		

*Note: Large size = 1880mmX2490mm, 1580mmX2490mm
 Extra large size = 2030mmX3050mm, 2000mmX3000mm
 Standard size = other sizes*

Cast Acrylic Sheet Chemical Features (Resistant Properties to Chemical Agents)

Sulfuric Acid	60°C	Stabile to 60%
Hydrochloric Acid	60°C	Stabile to 30%
Nitric Acid	60°C	Stabile to 20%
Caustic Soda	60°C	Stabile to 50%
Aqueous Ammonia	60°C	Stabile to 18%
Acetic Acid	60°C	Dissolve
Ethyl Acetate		Dissolve
Toluene		Dissolve
Ethylene Dichloride		Dissolve
Benzene		Dissolve
Methyl Alcohol		Dissolve
Dimethyl Formamide		Dissolve
Acetone		Dissolve
Aniline		Dissolve

Cast Acrylic Sheet Average Physical Properties

PROPERTIES	UNIT	
Specific Gravity		1.19
Hardness		HNC – 96
Water Absorption	%	0.35
Tensile Strength:		
Tensile strength at yield	Kg/cm²	709
Tensile strength of break	Kg/cm²	696
Tensile modulus	Kg/cm²	29,532
Elongation at break	%	8
Bending Strength:		
Flexual Strength	Kg/cm²	1.052
Flexual Modulus	Kg/cm²	31,264
Impact Strength	Kg/cm²	1.1
Shear Strength	Kg/cm²	600 – 650
Transmittancy:		
Full rays	%	93.3
Parallel rays	%	HAZE= 0.27
Specific Heat	Cal/g/°C	0.35
Heat Distortion Temperature (4.6kg/cm)	°C	100
Coefficient of Heat Conductivity	Cal/s.cm²	4.5 X 10⁻⁴
Coefficient of Linear Expansion	Cm/cm/°C	6.5 X 10⁻⁵
Ultimate Temperature of Continuous Operation	°C	60 – 90
Flammability	Mm/ min	33
Surface Resistivity at 28°C	Ohm	> 10¹⁶
Volume Resistivity	Ohm cm	> 10¹⁵
Thermoforming Ranges	°C	140 – 180
Dielectric Strength	Kv/Mm	20

MC Cast Acrylic Sheet meets Federal Specifications ASTM 4802 :

***Category A-1**—Methacrylate sheet typically manufactured by the cell-casting process. This category represents the best optical-quality sheet. It is characterized by the highest long-term design stress and the highest degree of chemical resistance found in methacrylate sheet.*

Cast Acrylic Sheet Fire Rating

Cast Acrylic Sheet burn with little smoke generation. Its combustions gases are non toxic and non corrosive. It is classed as:

- Classification E according to Euro Norm (DIN EN SO 11925: 2: 2002-07)
- B2, with no burning droplets, according to DIN 4102
- M4(no droplets) according to NF 92500+
- Class 3 classification according to BS476 part 7
- Category TP (b) according to BS 2782, method 508A for thermoplastics material as defined by Building Regulations
- UL 94HB