

Adjusting to your sign's needs in real time, ensuring steady, safe, and efficient illumination for optimal performance and longevity.





10-15 KV unit replaces 10,500V / 12,000V / 15,000V ratings



120V, 60hz, normal P.F.





5-9 KV unit replaces 5,000V / 6,000V / 7,500V / 9,000V ratings



Poly-resin filled



Available in Standard and Enclosed Case



2 year warranty

SELF-ADJUSTING NEON TRANSFORMERS

User Friendly Ground Fault Protection

Service Button: Allows the secondary ground fault protection (SGFP) mode to be bypassed for approximately 30 minutes. Note: The LED will blink Red if the unit has tripped and is not properly grounded. To prevent electrical shock hazard, the unit will not enter the bypass mode while improperly grounded.

Auto-Reset: The transformer will attempt to reset itself 3 times. The reset feature will help avoid nuisance tripping. The reset interval is approximately 3 seconds.

Diagnostic LED Operation:

power off and on

LED Mode Root Cause • LED Off Normal Operation Continuous Flashing Secondary Fault 1 Flash, Long Pause Transformer overheated 2 Flashes, Pause Transformer case missing service ground Transformer in bypass service mode LED ON To reset transformer, cycle

SPECIFICATIONS												
UNI-SERVE		Catalogue Number	Secondary		Primary	Input	Housing			Mounting		Wt.
			Volts kV	mA	V.A.	Amps	L	W	Н	MI	Mw	Lbs.
		101530BPX120 R	10-15	30	450	3.75	10.9"	4.2"	5.3"	9.6"	2.7"	22
		101530FPX120 R	10-15	30	450	3.75	12.5"	4.4"	6.8"	11.8"	2.5"	23
		5930CPX120 R	5-9	30	270	2.25	10"	3.6"	4"	8.7"	2"	12





